

PT100-WST4B



Display	Size	10.1" diagonal (16 : 9)
	Max. Resolution	1024 x 600
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	200
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM 32Bit 200MHz
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	8 MB (NOR Flash) + 128 MB (NAND Flash)
Real Time Clock (RTC)	Yes	
Communication Interface	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 RS232/RS485
COM3 RS232		
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	270.1 x 212.1 x 42.5
	Cutout Dimension WxH (mm)	259.5 x 201.5
	Net Weight (kg)	1.2 KG